

SAFETY DATA SHEET

# TESCO ECO GLASS CLEANER

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Tesco Eco Glass Cleaner

Company

Telephone

Fax

Emergency telephone number

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

### Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Ethanol	1 - 10%	64-17-5	200-578-6	F; R11
Alkoxy Ether Alcohol (2-(2-Butoxyethoxy) ethanol)	1 - 10%	112-34-5		Xi; R36

## 3. HAZARDS IDENTIFICATION

Main hazards No Significant Hazard

## 4. FIRST AID MEASURES

<b>Skin contact</b>	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
<b>Eye contact</b>	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
<b>Ingestion</b>	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing media</b>	Use extinguishing media appropriate to the surrounding fire conditions.
<b>Fire hazards</b>	Burning produces irritating, toxic and obnoxious fumes.
<b>Protective equipment</b>	Wear suitable respiratory equipment when necessary.

# TESCO ECO GLASS CLEANER

## 6. ACCIDENTAL RELEASE MEASURES

<b>Environmental precautions</b>	Do not allow product to enter drains. Prevent further spillage if safe.
<b>Clean up methods</b>	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Avoid contact with eyes and skin.
<b>Storage</b>	Keep containers tightly closed. Store in correctly labelled containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure limits

Ethanol	WEL 8-hr limit ppm: 1000 WEL 15 min limit ppm: -	WEL 8-hr limit mg/m <sup>3</sup> : 1920 WEL 15 min limit mg/m <sup>3</sup> : -
Alkoxy Ether Alcohol (2-(2-Butoxyethoxy) ethanol)	WEL 8-hr limit ppm: 10 WEL 15 min limit ppm: 15	WEL 8-hr limit mg/m <sup>3</sup> : 67.5 WEL 15 min limit mg/m <sup>3</sup> : 101.2

<b>Engineering measures</b>	Ensure adequate ventilation of the working area.
<b>Hand protection</b>	Chemical resistant gloves (PVC)
<b>Eye protection</b>	In case of splashing, wear: Approved safety goggles.
<b>Protective equipment</b>	Wear protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Description</b>	Liquid.
<b>Colour</b>	Colourless.
<b>Odour</b>	Alcoholic.
<b>pH</b>	6
<b>Boiling point</b>	100°C
<b>Vapour pressure</b>	1
<b>Freezing Point</b>	0°C

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Stable under normal conditions.
<b>Conditions to avoid</b>	Heat. Direct sunlight. Do NOT allow to freeze.

## 11. TOXICOLOGICAL INFORMATION

<b>Toxicological information</b>	No Significant Hazard.
----------------------------------	------------------------

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	No Significant Hazard.
--------------------	------------------------

## 13. DISPOSAL CONSIDERATIONS

<b>General information</b>	Dispose of in compliance with all local and national regulations.
----------------------------	---

## 14. TRANSPORT INFORMATION

<b>Further information</b>	The product is not classified as dangerous for carriage.
----------------------------	--

## 15. REGULATORY INFORMATION

<b>Risk phrases</b>	NSH - No Significant Hazard.
---------------------	------------------------------

# TESCO ECO GLASS CLEANER

## 16. OTHER INFORMATION

**Text of risk phrases in  
Section 2**

R11 - Highly flammable.  
R36 - Irritating to eyes.

**Further information**

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.